

Floodlight Series



LT-H0204-120

FEATURES AND SPECIFICATIONS

Application

Professional lighting for environments like museums, art galleries, outdoor signages of retail shops, exhibition booths, etc. Good option to replace traditional MH and HPS lights.

2700K-3500K/4000K-5000K/5000K-6500K

45°/60° (H Series)

24°/36°/60°/90°(NH Series)

AC100-240V 50/60Hz

110-120lm

CRI 70-90

Lifespan >50000h

Work Temp -40~50°C

Product Parameters

Model	LT-H0102-60	LT-H0103-90	LT-H0204-120	LT-H0208- 240
Power	60W	90W	120W	240W
Power Factor	>0.9			
IP Rating	IP 65			
Operating Temperature	-40°~ 50°C			
Anti-electric shock Rate	Grade I			
Lifespan	>50000 hours			
Color Temperature	2400-7000K (Optional according to guest's need)			
Input Voltage	100-240VAC 50/60Hz			
Material	Aluminum Alloy			

Net Weight	3.3±0.2KG	4.275±0.2KG	6±0.2KG	9.75±0.2KG
size	L260*W207*H140	L400*W207*H140	L424*W256*H195	L531*W424*H213

Model	LT-NH0202-T1-60	LT-NH0103-T1-90	LT-NH0104-T1-120	LT-NH0105-T1-150
Power	60W	90W	120W	150W
Power Factor	>0.9			
IP Rating	IP 65			
Operating Temperature	-40°~ 50°C			
Anti-electric shock Rate	Grade I			
Lifespan	>50,000 hours			
Color Temperature	2400-7000K (Optional according to guest's need)			
Input Voltage	100-240VAC 50/60Hz			
Material	Aluminum Alloy			
Net Weight	3.9±0.2KG	4.41±0.2KG	5.24±0.2KG	5.84±0.2KG
Size	L577*W175*H172	L300*W210*H150	L430*W260*H150	L315*W230*H170