

Tunnel Light Series



LT-NH0202-T1-60

FEATURES AND SPECIFICATIONS

Application

Great lighting for tunnels, toll station, platform, underpass, warehouse, sport area, billboard, and architectural buildings, an easy and good replacement for traditional MH or HPS lamps.

2400K-3500K/3500K-4500K/5000K-6500K/6500-7000K

45°/60° (H Series) ; 24°/36°/60°/90°(NH Series)

AC100-240V 50/60Hz

100-120lm/W

IP65 Power Factor >0.95

Lifespan >50000h

Work Temp -40~50°C

Anti-electric shock Rate: Grade I

Product Parameters

Model	LT-H0102-60	LT-H0103-90	LT-H0204-120
Power	60W	90W	120W
Power Factor	>0.9		
IP Rating	IP 65		
Operating Temperature	-40°~ 50°C		
Anti-electric shock Rate	Grade I		
Lifespan	>50000 hours		
Color Temperature	2400-7000K (available options)		
Input Voltage	100-240VAC 50/60Hz		
Material	Aluminum Alloy		
Net Weight	3.3±0.2KG	4.275±0.2KG	6±0.2KG
Size	L260*W207*H140	L400*W207*H140	L424*W256*H195

Model	LT-NH0202-T1-60	LT-NH0102-T1-60	LT-NH0103-T1-90	LT-NH0104-T1-120
Power	60W	60W	90W	120W
Power Factor	>0.9			
IP Rating	IP 65			
Operating Temperature	-40°~ 50°C			
Anti-electric shock Rate	Grade I			
Lifespan	>50,000 hours			
Color Temperature	2400-7000K (available options)			
Input Voltage	100-240VAC 50/60Hz			
Material	Aluminum Alloy			
Net Weight	3.9±0.2KG	3.9±0.2KG	4.41±0.2KG	5.24±0.2KG
Size	L577*W175*H172	L315*W230*H170	L300*W210*H150	L430*W260*H150