

# Wall Washer Series



LT-F61-10-30



LT-F62-10-18



LT-F63-10-18



LT-F64-10-24



LT-F65-10-30



LT-F66-10-24

## FEATURES AND SPECIFICATIONS

### Application

General outdoor lighting for landscape, billboard, architecture, building walls, parking lot, gymnasium, dock, park, tree decoration and alike.

10° /30° /45° /60° /90° /120 °

(elect)

2700K-3500K/4000K-5000K/5000K-6500K

AC100-240V 50/60Hz

60-70lm

CRI 70-85

Lifespan > 50000h

Work Temp -40~50°C

### Product Parameters

Model	LT-F61-10-30	LT-F62-10-18	LT-F63-10-18	LT-F64-10-24
Power	30W	18W	18W	24W
Power Factor	>0.9			
IP Rating	IP 67			
Operating Temperature	-40°~ 50°C			
Anti-electric shock Rate	Grade I			

Lifespan	> 50000 hours			
Color Temperature	2400-7000K (available options)			
Input Voltage	AC100-240V 50/60hZ			
LED Illumination	110-140 lm			
Lamp Efficiency	70-90 lm/w			
CRI	70-85			
Dimension(mm)	L1000			
Net Weight	1.55kg±0.2kg	1.95kg±0.2kg	1.85kg±0.2kg	1.8kg±0.2kg

Model	LT-F65-10-30	LT-F66-10-24
Power	30W	24W
Power Factor	>0.9	
IP Rating	IP 67	
Operating Temperature	-40°~ 50°C	
Anti-electric shock Rate	Grade I	
Lifespan	> 50000 hours	
Color Temperature	2400-7000K (available options)	
Input Voltage	100-240VAC 50/60Hz	
LED Illumination	110-140 lm	
Lamp Efficiency	70-90 lm/w	
CRI	70-85	
Dimension(mm)	L1000	
Net Weight	2.3kg±0.2kg	1.55±0.2KG